

MDC-6210F-24

BULLET CAMERA





GENERAL FEATURUES

- 1/3" SONY Super HAD Color CCD (270K Pixels)
- 380 TV Lines
- Built-in 6mm Fixed Lens (Standard)
- Built-in 24pcs IR LEDs
- Excellent Auto Tracking White Balance, etc.
- Weatherproof Housing (IP66)
- DC12V Power Source



DIMENSIONS(mm)



New Design



SPECIFICATIONS

MODEL	MDC-6210F-24	
ITEM	NTSC	PAL
Image Sensor	1/3" Sony Super HAD Color CCD	
Effective Pixel	510(H) x 492(V)	500(H) x 582(V)
Scanning System	525 Lines 2:1 Interlace	625 Lines 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94Hz (V)	15.625KHz (H), 50Hz (V)
Resolution	380TV Lines	
Shutter Speed	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
S/N Ratio	More than 50dB (AGC off)	
Sync System	Internal	
Lens	6mm Fixed (Standard)	
Min. Illumination	0.3 Lux(Color) at F 1.2 / 0 Lux at IR-Led ON	
White Balance	ATW / AWC / MANUAL	
Video Output	Composite 1.0Vp-p(75Ω load)	
Power Supply	DC12V ±10%	
Operating Temp.	-10°C ~ +50°C	
Operating Humidity	90% RH max.	
Dimension (m/m)	φ50	