

# MDC-7220TDN

## DOME CAMERA






### GENERAL FEATURUES

- 1/3" SONY Super HAD Color CCD (410K Pixels)
- More than 580 TV Lines (color), 700 TV Lines (B/W)
- Disk saving with DNR Technology
- Low Sensitivity of 0.001 Lux (Sens-up)
- Built-in 2.8~11mm Filter changeable Varifocal DC Auto Iris Lens
- Multi OSD function built-in
  - Privacy, Motion Detection, HLC etc.
- $\phi$ 120 Indoor Dome Housing
- DC12V Power Source



### DIMENSIONS(mm)



( $\phi$ 100, 3Axis)



( $\phi$ 120, 3Axis)

### SPECIFICATIONS

MODEL	MDC-7220TDN	
ITEM	NTSC	PAL
Image Sensor	1/3" Sony Super HAD Color CCD	
Effective Pixel	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Scanning System	525 Lines 2:1 Interlace	625 Lines 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94Hz (V)	15.625KHz (H), 50Hz (V)
Resolution	More than 580TV Lines (Color), 700TV Lines (B/W)	
Shutter Speed	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
S/N Ratio	More than 52dB (AGC off)	
Sync System	Internal	
Lens	2.8~11mm ICR Varifocal DC Auto Iris Lens	
Min. Illumination	0.15 Lux(Color) / 0.03 Lux(B/W) / 0.001(Sens-up) at F 1.2	
White Balance	ATW / AWC / MANUAL / OUTDOOR / INDOOR	
Video Output	Composite 1.0Vp-p(75 $\Omega$ load)	
Power Supply	DC12V $\pm$ 10%	
Operating Temp.	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C	
Operating Humidity	90% RH max.	
Dimension (m/m)	120mm Dome size	