

MDR-4700 / MDR-8700 / MDR-16700

DVR



GENERAL FEATURUES

- Pentaplex 4 / 8 / 16 Channel
- OSD Menu controllable by Keyboard Controller
- Storage : SATA HDD Max 1TB x 2
- VGA Support / Spot Monitor Output Mode
- MPEG-4 ASP Records and Plays in High-definition Video
- Static IP, DHCP, DDNS Support
- POS . ATM (Patent Pending, Optional)
- E-mail Notification (video Clip, Still Image, Message)
- NTP (Network Time Protocol)

DIMENSIONS(mm)

MDR-4700



MDR-8700



MDR-16700



SPECIFICATIONS

| MODEL | MDR-4700 | MDR-8700 | MDR-16700 |
|-------------------------|--|------------------------|-------------------------|
| Compression | Advanced MPEG4 ASP | | |
| Signal Format | NTSC or PAL (Auto Selected) | | |
| Video Input | Composite 4 BNC Inputs | Composite 8 BNC Inputs | Composite 16 BNC Inputs |
| Video Output | Composite: 1 (1Vp-p, 75 Ohm) | | |
| VGA Output | 1 VGA | | |
| Recording Resolution | 704 x 480, 704 x 240, 352 x 240 (NTSC) / 704 x 576, 704 x 288, 352 x 288 (PAL) | | |
| Recording Frame Rate | NTSC | 352 x 240 : 120FPS | 352 x 240 : 240FPS |
| | PAL | 352 x 288 : 100FPS | 352 x 288 : 200FPS |
| Audio Input | 1 Input (RCA Jack) | | |
| Audio Output | 1 Output (RCA Jack) | | |
| Ethernet | 10 / 100Mbps Ethernet (RJ-45) | | |
| PTZ Control | RS-485 / 422 Serial Port 1 (Terminal Block) | | |
| Alarm Input / Output | 4 (TTL) Programmable as NC / NO | | |
| USB Port | 4 x USB 2.0 (2 x Front Panel, 2 x Rear Panel) | | |
| Recording Modes | Schedule / Alarm / Motion / Emergency | | |
| Pre-Alarm Recording | up to 3 Hours / User Programmable | | |
| Emergency Recording Key | Yes | | |
| Primary Storage | SATA Hard Disk Drive up to 2HDD | | |
| Clip Copy Storage | Built-in Internal CD-RW or DVD/CD-RW Driver, Via USB HDD, Memory Stick | | |
| Operating Temperature | 5C ~ 40C / 41F ~ 104F | | |
| Power Adapter | Free Voltage 12VDC, 5A | | |
| Dimension(WxHxD) | 350 mm x 65 mm x 380 mm | | |