

MDR-4800 / MDR-8800 / MDR-16800

DVR



GENERAL FEATURUES

- Pentaplex 4 / 8/ 16 Channel
- OSD Menu Controllable by Keyboard Controller
- Storage: SATA HDD MAX 1TB x 4
- VGA Support / Spot Monitor Output Mode
- MPEG4 ASP Records and Plays in High-definition Video
- Static IP, DHCP, DDNS Support
- POS / ATM (Patent Pending, Optional)
- E-mail Notification (Video Clip, Still Image, Message)
- NTP (Network Time Protocol)

DIMENSIONS(mm)

MDR-4800



MDR-8800



MDR-16800



SPECIFICATIONS

MODEL	MDR-4800	MDR-8800	MDR-16800
Compression	Advanced MPEG4 ASP		
Signal Format	NTSC or PAL (Auto Selected)		
Video Input	Composite 4 BNC Inputs	Composite 8 BNC Inputs	Composite 16 BNC Inputs
Video Output	Composite: 1 (1Vp-p, 75 Ohm)		
Loop Output	4 BNC Looping Outputs	8 BNC Looping Outputs	16 BNC Looping Outputs
Spot Output	1 BNC	3 BNC	3 BNC
SVHS Output	1 (SVHS)		
VGA Output	1 VGA		
Recording Resolution	704 x 480, 704 x 240, 352 x 240 (NTSC) / 704 x 576, 704 x 288, 352 x 288 (PAL)		
Recording Frame Rate	NTSC	704 x 240 : 120FPS	352 x 240 : 240FPS
	PAL	704 x 288 : 100FPS	352 x 288 : 200FPS
Audio Input	4 Inputs (RCA Jack)	8 Inputs (RCA Jack)	8 Inputs (RCA Jack)
Audio Output	1 Output (RCA Jack)		
Ethernet	10 / 100Mbps Ethernet (RJ-45)		
PTZ Control	RS-485 / 422 Serial Port 1 (Terminal Block)		
Alarm Input	4 (TTL) Programmable as NC / NO	8 (TTL) Programmable as NC / NO	16 (TTL) Programmable as NC / NO
USB Port	4 x USB 2.0 (2 x Front Panel, 2 x Rear Panel)		
Recording Modes	Schedule / Alarm / Motion / Emergency		
Pre-Alarm Recording	Up to 3 Hours / User Programmable		
Primary Storage	SATA Hard Disk Drive (up to 4+0 or 3+1)		
Clip Copy Storage	Built-in Internal CD-RW or DVD/CD-RW Driver, Via USB HDD, Memory Stick		
Dimension(WxHxD)	430 mm x 88 mm x 400 mm		